


DANIELE & GIRAUDD

Decespugliatrice - Hydraulic flail-hedger mower – Débroussailleuse

DG40100-DG45100-DG50100



	A(mm)	B(mm)	C(mm)	D(mm)	E(mm)	F(mm)	G(mm)
DG40100	4100	3700	2900	3800	2100	1500	1000
DG45100	4600	4200	3400	4300	2350	1700	1000
DG50100	5100	4700	3900	4800	2600	1900	1000

Mod.



OIL



	Code	Kg	Rpm	Rpm	HP	HP	Lt	Kg	Cm	HP
DG40100	BTE018DG	660	540	3000	45	40	190	2000	160	50-60
DG45100	BTE019DG	700	540	3000	45	40	190	2500	170	60-70
DG50100	BTE020DG	740	540	3000	45	40	200	2800	170	60-80

Decespugliatrice idraulica per trattori di media potenza, adatta alla pulizia di argini, fossi e bordi stradali.

Hedge-cutter for medium power tractors, suitable for cleaning embankments, ditches and road edges.

Débroussailleuse hydraulique pour tracteurs de moyenne puissance, adaptée au nettoyage des talus, des fossés et des bords de route.



Rotore reversibile

Reversible rotor

Rotor réversible

-serbatoio con olio idraulico;

-comando a 4 leve con cavi flessibili da mm 3000;

-impianto idraulico indipendente;

-dispositivo antiurto meccanico;

-registrazione del rullo in altezza;

-trasmissione diretta;

-sistema flottante sulla testata;

-reversibilità del rotore;

-pattini antiusura;

-tank with hydraulic oil;

-4-lever control with flexible cables of 3000mm;

-independent hydraulic system;

-mechanical shockproof device;

-registration of the roller in height;

-direct transmission;

-floating system on the head;

-reversibility of the rotor;

-wear-resistant pads;

-réservoir d'huile hydraulique;

-Commande à 4 leviers avec câbles flexibles de 3000mm;

-système hydraulique indépendant;

-dispositif antichoc mécanique;

-enregistrement du rouleau en hauteur;

-transmission directe;

-système flottant sur la tête;

-réversibilité du rotor;

-patins anti-usure;



GRUPPO TRINCIATURA	CUTTING UNIT	GROUPE DE BROYAGE	DG40100	DG45100	DG50100
Larghezza di lavoro(mm)	Working width	Largeur de travail	1000	1000	1000
Angolo di rotazione del gruppo(°)	Group rotation angle	Angle de rotation du groupe	180°	180°	180°
Diametro di taglio(mm)	Cutting diameter	Diamètre de coupe	380	380	380
Diametro del rotore nudo(mm)	Bare rotor diameter	Diamètre rotor nu	82	82	82
Spessore del rotore(mm)	Rotor thickness	Épaisseur du rotor	10	10	10
Coltelli snodati a Y+I	Y+I-jointed knives	Couteaux à joint en Y+I	32+16	32+16	32+16
Velocità di rotazione del rotore(rpm)	Rotor rotation speed	Vitesse de rotation des rotors	3000	3000	3000
Tipo di trasmissione dell'albero	Type of shaft	Type de transmission par arbre	Diretta	Direct	Direct
Diametro del rullo posteriore(mm)	Rear roller diameter	Diamètre du rouleau arrière	120	120	120



DANIELE & GIRAUDO

Via Levaldigi,9

12020-Vottignasco-Italy

www.danieleegirauddo.com – info@danieleegirauddo.com